



#### INITIAL CONSTRUCTION CLEAN

- Sweep, mop sweep or dry vacuum the floor to remove dust, grit and debris.
  - For light soiling, damp mop the floor with a neutral cleanser diluted to the manufacturer's instructions.
- OR
- For heavy soiling, apply a solution of alkaline cleanser, diluted to the manufacturer's instructions, to the floor and leave for sufficient time to react with the soiling. Using a 450 rpm rotary machine, scrub the floor and then pick up the slurry with a wet vacuum. Rinse the floor thoroughly with clean warm water, pick up with a wet vacuum and leave to dry thoroughly.



#### ROUTINE MAINTENANCE

- The following recommendations are provided as a guideline, and the frequency can be changed to optimise the appearance.
  - Assess daily the appearance of the floor. Undertake the following as required:
  - Light scuffing - spray clean using a solution of a neutral cleaner diluted to the manufacturer's instructions and a 450 rpm plus rotary machine fitted with a suitable clean buffing pad.
- OR
- Heavier scuffing - spray clean using a solution of an alkaline cleaner diluted to the manufacturer's instructions and a 450 rpm plus rotary machine fitted with a suitable clean scrubbing pad.

**NOTE:** In most instances, the above maintenance regime will be sufficient to ensure your floorcovering retains the optimum appearance. However where there is no mechanical means of maintaining the floor, a conductive polish should be applied.



#### APPLICATION OF A FLOOR DRESSING

- Ensure there is a good key between the floor dressing and the surface of the flooring, scrubbing the floor if required.
- Either of the following methods can be used:
- Conductive polish. Apply two or three thin coats of an approved conductive polish, in accordance with the manufacturer's instructions, with either a proprietary polish applicator or Kentucky mop wrung out to prevent over-application of polish. The polish should be applied up to 150mm from the edges of the room and subsequent coats should be applied at 90° to the previous one. The final coat should be applied right up to the edges of the room.



- Always ensure mops and pads are kept especially for the static control areas, to prevent a possible transfer of polish.
  - Always follow the Health and Safety guidance provided.
  - At the date of issue the data presented is correct. However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.
  - For further clarification and advice on specific applications, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.
- REGULAR CLEANING IS MORE BENEFICIAL TO THE FLOORCOVERING AND MORE COST-EFFECTIVE THAN OCCASIONAL HEAVY CLEANING.**
- To confirm details of conductive polishes which are approved for use with Polyflor OHMega EC:  
Statguard Polish and Statguard Low VOC Polish -  
from Charleswater/Vermason +44 (0)1892 665 313.  
Taski Jontec ESD Polish from Diversey +44 (0)1604 405 311

POLYFLOR

# OHMega EC

## FLOORCARE

# APPROVED MAINTENANCE PRODUCTS

The companies listed have products that are approved for use with Polyflor products. For full instructions for use, and health and safety guidelines, please contact the manufacturer.

## MAINTENANCE PRODUCTS

PRODUCT	DR. SCHUTZ Tel: 01296 437827 www.dr-schutz.com	BRITISH NOVA Tel: 01295 254030	PROCHEM Tel: 0208 974 1515 www.prochem.co.uk	EVANS VANODINE Tel: 01772 322200 www.evansvanodine.co.uk	ECOLAB LTD Tel: 01793 511221 www.ecolab.com	DIVERSEY UK LTD Tel: 01604 405311 www.diversey.com	SELDEN RESEARCH Tel: 01298 26226 www.selden.co.uk
NEUTRAL CLEANSER	Active Cleaner	Liquid 99	Prodet	High Class	Brial Action Plus	Taski Jontec 300  Carefree Stride 1000	Neutral Scrubber Drier Detergent  Sabre
ALKALINE CLEANSER	Clean and Strip	Novaways  Novaways Multi Purpose Sanitiser	Alkleen  Ultrapac Renovate  Powerclean	E.M.C Plus  Versatile  Lift  HSC	Gloss Express  Regain Regain Ultra Powerclean Imi Action Plus	Brillo Cleaner/ Degreaser  Carefree Stride 2000  Sprint Hard Surface Cleaner Taski Jontec Forward	Multi-Purpose Cleaner  Selcien S  Triple
GERMICIDAL CLEANSER		Novacross Non food areas  Novacross (unperfumed) Food areas	Protect	Final Touch  Safe Zone  Protect		Lifeguard Cleaner/ /Disinfectant Conc.  Shield  Lifeguard cleaner Disinfectant Trigger	Selgiene  Selgiene Ultra  Selective
MAINTAINER/ WASH & WAX	Floor Cleaner R1000	Novacare  Novacare Lime-lite	Protreat	Clean & Shine	Indur XL Fresh  Indur Brilliant Plus  Satine Brilliant Plus Indur Restorer Spray	Carefree Maintainer  Carefree Mop & Shine  Carefree Stride 3000 Taski Tensol	Selsheen  Fast Lane  Low Foam Floor Maintainer
DRY BRIGHT EMULSION POLISH	Floor Shine	Nova Long Life  Nova Long Life Satin Finish	Proshine	Sustain  Mexepol  Enhance	Isi Star  Phazer Isi Star  Gemstor Laser  Satin Star Tuklar Medical	Carefree Satin Carefree Eturnum Carefree Emulsion	Seldur Selexel Diamond Brite
SEMI BUFFABLE EMULSION POLISH	Floor Mat	Nova Supercote				Carefree Buffable Floor Polish	Selglo
FULLY BUFFABLE EMULSION POLISH	Secura Hard Sealer	Nova Superphalte	Proshine		Tuklar Medical		
POLISH STRIPPER	Clean & Strip	Nova Starbrite  Nova 2001	Prostrip	Easystrip  Sure Strip	Benduroil Maxx Benduroil Forte  Benduroil Top Strip	Carefree Stripper  Carefree Speed Stripper	Selstrip Selspeed Selate
POWER CLEANER (Spot Cleaner)	Turbo Strip	Cleanol Lift	Superclean	Lift		Sprint Spitfire	Maxima

The data presented is correct at the time of printing. However, Polyflor Ltd. reserves the right to update this information as and when necessary.

For the latest information, please check our web site at [www.polyflor.com](http://www.polyflor.com)

Polyflor Ltd, in providing this information, does not imply any equivalence between each of the different manufacturers' products, or that other products would prove unsatisfactory.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551  
 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912  
 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128  
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: [INFO@POLYFLOR.COM](mailto:INFO@POLYFLOR.COM)  
 WEBSITE: [WWW.POLYFLOR.COM](http://WWW.POLYFLOR.COM)

*James Helstead*  
FLOORING



2011

**POLYFLOR**  
COVERING THE WORLD