

AFFINITY 2⁵⁵ PUR

- Authentic reproductions of classic and contemporary wood planks
- Luxury vinyl tile collection ideal for heavy commercial interiors
- Developed to blend seamlessly with 2mm vinyl sheet flooring

SPECIFICATION



2.0mm



0.55mm



15 @ 184.2 x 1219.2mm = 3.37m²



3500g/m²



GENERAL PERFORMANCE

EN 649

EN ISO 10582



REACTION TO FIRE

EN ISO 13501-1 Class Bfl-S1



ABRASION RESISTANCE

EN 649 Group T

EN ISO 10582 Type 1



SLIP RESISTANCE*

EN 13893 Class DS (dry condition)

DIN 51130 R10

For safety flooring with sustainable wet slip resistance, refer to Expona Control PUR or the Polysafe ranges



ELECTRICAL BEHAVIOUR (body voltage)

EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



INDENTATION - RESIDUAL

EN 433 ≤0.1mm

EN ISO 24343-1 ≤0.1mm



DIMENSIONAL STABILITY

EN 434 <0.25%

EN ISO 23999 ≤0.25% max.



CASTOR CHAIR (continuous use)

EN 425 / ISO 4918 Suitable



THERMAL CONDUCTIVITY

Suitable for underfloor heating
heating Max 27°C



LIGHT FASTNESS

ISO 105-B02 (Method 3) ≥6



RESPONSIBLE SOURCING

BES 6001 Very good

SA 8000 Approved factory



VOC EMISSIONS

Indoor Air Comfort GOLD - Eurofins certified product

AgBB - Very low emissions

FloorScore - Certified product



ENVIRONMENTALLY PREFERABLE FLOORING

Affinity 2⁵⁵ PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 429). EN 15804 Environmental Product Declaration (EPD) is available on request. Affinity 2⁵⁵ PUR is 100% recyclable and contains average 40% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



APPLICATIONS

Affinity 2⁵⁵ PUR is ideal for heavy commercial areas within the retail, office, leisure, healthcare, education and housing sectors.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

* For clarification regarding slip resistance, consult Polyflor.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THESE PRODUCTS INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
 WEBSITE: WWW.POLYFLOR.COM

James Halstead
 FLOORING



2011



Recofloor™
 Vinyl Take-Back Scheme



Affinity2⁵⁵



PERFORMANCE AND PROPERTIES




ENP 429
 ENVIRONMENTAL
 RATING

Refer to BRE Global ratings
 on www.greenbooklive.com



In collaboration with the European Resilient Flooring
 Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable
 construction via Environmental Product Declarations (EPDs).



POLYFLOR™
 COVERING THE WORLD