



- Polyflor Affinity2⁵⁵ PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits and life cycle maintenance savings.
- The following maintenance instructions are designed to minimise the cost factor, without compromising the long-term appearance of your floorcovering.

**INITIAL CONSTRUCTION CLEAN**

- Remove all loose debris.
- Ensure that all traces of adhesive are removed from the surface of the floorcovering.
- Mop sweep or vacuum to remove dust and grit.
- Damp mop with a neutral detergent.
- If required, dry buff with a 1000 rpm plus rotary machine fitted with a suitable clean pad.

**ROUTINE MAINTENANCE**

- The following recommendations are provided as a guideline, and the frequencies can be changed to optimise the appearance.

DAILY

- Mop sweep or vacuum to remove dust and loose dirt.
- If required, spot clean to remove stubborn marks with a neutral cleanser.
- If required, dry buff to restore finish.

WEEKLY/MONTHLY

- Assess the appearance of the floor.
- If required, scrub with a scrubber dryer fitted with suitable pads, and using neutral cleanser (pH 7 to 9).
- If required, dry buff to restore finish.

**APPLICATION OF A FLOOR DRESSING**

- Should you wish to apply a floor dressing to the floorcovering to provide extra protection in heavily trafficked areas, please follow details of the procedure below.
- Using an applicator and tray, or Kentucky mop with wringer and bucket, the first coat should be applied thinly and evenly across the floor, to within 200mm of the skirtings. It should then be left to dry. This normally takes approximately thirty minutes, depending on the ambient conditions and the thickness of the coating.
- When the first coat is dry, a second coat should be applied at right angles to the direction of the first. Subsequent coats should be applied at right angles, and the final coat should be applied right up to the skirting.
- Two to three thin coats are usually sufficient to provide excellent resistance to abrasion, scuffing and removal of black heel marking. However, be guided by your own periodic assessments for the particular location.
- In order to minimise costs, subsequent polish applications may be applied only to traffic paths.
- Periodically - generally every six months - assess the appearance of the floor. If there is an unacceptable build-up of polish, this should be stripped and reapplied, as per the instructions above.



NOTE: The maintenance regime requires the installation of an effective barrier matting system.

- Cleaners and detergents should be diluted as per the manufacturer's instructions. These maintenance instructions are intended for Polyflor Affinity2⁵⁵ PUR, which incorporates a polyurethane reinforcement. For other Polyflor products, reference should be made to their specific floorcare sheets.
 - For further information and advice on specific applications, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com. Always follow the Health and Safety guidance provided.
 - At the date of issue the data presented is correct. However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.
- REGULAR CLEANING IS MORE BENEFICIAL TO THE FLOORCOVERING AND MORE COST-EFFECTIVE THAN OCCASIONAL HEAVY CLEANING.**

Affinity2⁵⁵



FLOORCARE

APPROVED MAINTENANCE PRODUCTS

The companies listed have products that are approved for use with Polyflor products. For full instructions for use, and health and safety guidelines, please contact the manufacturer.

MAINTENANCE PRODUCTS

| PRODUCT | DR. SCHUTZ Tel: 01296 437827 www.dr-schutz.com | BRITISH NOVA Tel: 01295 254030 www.cleenol.co.uk/britishnova/ | PROCHEM Tel: 0208 974 1515 www.prochem.co.uk | EVANS VANODINE Tel: 01772 322200 www.evansvanodine.co.uk | ECOLAB LTD Tel: 01793 511221 www.ecolab.com | DIVERSEY UK LTD Tel: 01604 405311 www.diversey.com | SELDEN RESEARCH Tel: 01298 26226 www.selden.co.uk |
|--------------------------------|--|---|--|--|---|---|---|
| NEUTRAL CLEANSER | Active Cleaner | Liquid 99 | Prodet | High Class | Brial Action Plus | Taski Jontec 300 Carefree Stride 1000 | Neutral Scrubber Drier Detergent Sabre |
| ALKALINE Cleanser | Clean and Strip | Novaways Novaways Multi Purpose Sanitiser | Alkleen Ultrapac Renovate Powerclean | E.M.C Plus Versatile Lift HSC | Gloss Express Regain Regain Ultra Powerclean Imi Action Plus | Brillo Cleaner/Degreaser Carefree Stride 2000 Sprint Hard Surface Cleaner Taski Jontec Forward | Multi-Purpose Cleaner Selcien S Triple |
| GERMICIDAL CLEANSER | | Novacross Non food areas Novacross (unperfumed) Food areas | Protect | Final Touch Safe Zone Protect | | Lifeguard Cleaner/Disinfectant Conc. Shield Lifeguard cleaner Disinfectant Trigger | Selgiene Selgiene Ultra Selective |
| MAINTAINER/Wash & Wax | Floor Cleaner R1000 | Novacare Novacare Lime-lite | Protreat | Clean & Shine | Indur XL Fresh Indur Brilliant Plus Satine Brilliant Plus Indur Restorer Spray | Carefree Maintainer Carefree Carefree Stride 3000 Taski Tensol | Selsheen Fast Lane Mop & Shine Low Foam Floor Maintaine |
| DRY BRIGHT EMULSION POLISH | Floor Shine | Nova Long Life Nova Long Life | Proshine Satin Finish | Sustain Mexepol Enhance | Isi Star Phazer Isi Star Gemstor Laser | Carefree Satin Carefree Eturnum Carefree Emulsion Satin Star Tuklar Medical | Seldur Selxel Diamond Brite |
| SEMI BUFFABLE EMULSION POLISH | Floor Mat | Nova Supercote | | | | Carefree Buffable Floor Polish | Selglo |
| FULLY BUFFABLE EMULSION POLISH | Secura Hard Sealer | Nova Superphalte | Proshine | | Tuklar Medical | | |
| POLISH STRIPPER | Clean & Strip | Nova Starbrite Nova 2001 | Prostrip | Easystrip Sure Strip | Bendurol Maxx Bendurol Forte Bendurol Top Strip | Carefree Stripper Carefree Speed Stripper | Selstrip Selspeed Selate |
| POWER CLEANER (Spot Cleaner) | Turbo Strip | Cleanol Lift | Superclean | Lift | | Sprint Spitfire | Maxima |

The data presented is correct at the time of printing. However, Polyflor Ltd. reserves the right to update this information as and when necessary.

For the latest information, please check our web site at www.polyflor.com

Polyflor Ltd, in providing this information, does not imply any equivalence between each of the different manufacturers' products, or that other products would prove unsatisfactory.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
 WEBSITE: WWW.POLYFLOR.COM

James Halstead
FLOORING



2011

POLYFLORTM
COVERING THE WORLD