

DECLARATION OF PERFORMANCE James Halstend



DOP CAMARO LOC - Loose Laid Clic Luxury Vinyl Tile Flooring

Unique identification code of the product-type:

FCaL-DoP-001

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

CAMARO LOC - Loose Laid Clic Luxury Vinyl Tile (EN ISO 10582 / EN 14085)

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.

Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

James Halstead PLC, Beechfield, Hollinhurst Road, Radcliffe, Manchester, M26 1JN, United Kingdom

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

James Halstead PLC, Beechfield, Hollinhurst Road, Radcliffe, Manchester, M26 1JN, United Kingdom

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

In case of the declaration of performance concerning a construction product covered by a harmonised standard: Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).

> Exova Warringtonfire Holmesfield Road. Warrington, WA1 2DS Notified Body 0833

not applicable

certificate of constancy of performance

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not applicable

9.	Declared performance		
	Essential characteristics	Performance	Harmonised technical specification
	Reaction to fire	B _{II} -S1	EN 14041: 2004/AC:2006
	Content of Pentachlorophenol	° DL PCP	EN 14041: 2004/AC:2006
	Formaldehyd Emissions	° NA HCHO	EN 14041: 2004/AC:2006
	Slip resistance	DS DS	EN 14041: 2004/AC:2006
	Electrical behavior (dissipative)	NPD	EN 14041: 2004/AC:2006
	Electrical behavior (conductive)	NPD	EN 14041: 2004/AC:2006
	Electrical behavior (antistatic)	NPD	EN 14041: 2004/AC:2006
	Thermal conductivity [W/mK]	0.25 W/m.K	EN 14041: 2004/AC:2006
	Water-tightness	NPD	EN 14041: 2004/AC:2006

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4 Signed for and on behalf of the manufacturer by:

Steve Mulholland, Group Technical Manager (name and function)

23rd September 2014, Manchester, UK

S Mulholland

(signature)