



GENERAL INFORMATION PRODUCTS MODEL ZK-T

Description

- Horizontal wall protector, composed of an inner plastic profile, anchored on the face by means of a standard 6mm double fixing, appropriate to the support, every approximately 900mm.
- At each end of the Zikonyl ® profile are placed 2 ZK413 finishing caps manufactured by injection of PA and PP modified to the impact to give it greater robustness.
- Both the Zikonyl ® ZK204 coating and the inner profile are made of impact and fire resistant PVC, 2mm thick, colored in mass and with a textured face to hide scratches and a non-porous surface, PVC is a material gives it the necessary resistance to withstand the strongest blows, and PVC is a material that easily recovers its original shape.

Technical Characteristics

Plastic Zikonyl ®

- PVC from virgin material, our material is free of phthalates.
- PVC that comes from virgin material, not recycled, since in doing the protection with recycled material this loses a great part of its technical characteristics, in addition it complies with that specified in the Directive 2011/65 / UE (RoHS Directive), on restrictions to the use Of certain dangerous substances in electrical and electronic equipment, Annex II, as amended by Directive 2015/863.
- It is classified according to the regulation (CE) n° 1272/2008 as prepared non dangerous.

Mechanical properties PVC

Properties	Value	Measurement units	Normative
Vicat Temperature (5 kg)	Minimum 80	°C	UNE EN ISO 306
Density	1,39 - 1,45	G/cm ³	UNE EN ISO 1183
Tensile Strength	Minimum 40	Mpa	UNE EN ISO 527

Cleaning

- For a correct state of preservation of the Zikonyl ® profiles, a wash with soap and water is sufficient, and if necessary, rub it with a soft plastic barbed brush. You can also use specific cleaning products for plastic such as Power32 or similar. Do not use bleach, or products derived from hydrochloric acid, for the cleaning of the end caps, or for the separating supports. This would cause a whitening of your surface face.

Certificates

- With reference to the fireproofing tests, we have the M1 classification according to UNE 23727: 1990, currently working with the fire reaction classification according to UNE 13501-1: 2002 and tests have been carried out with the classification: C-s3.d2 of which are excluded covers, anchors or any other small type of accessory. These values are approximate and may vary according to the type of application.
- We have the certificate of Quality in accordance with the requirements of the standard UNE-EN ISO 9001:2008.

Environment

- All materials used in the manufacture of Zikonyl ® are considered as inert product according to the Waste Law 22/2011, so they are fully recyclable and respectful with the environment.
- Likewise all the waste generated during the preparation of the orders are gathered for its due management and destruction, according to the current legal regulations.

Guarantee

All our products have a warranty of two years, from the date of supply for any manufacturing defect thereof. This warranty shall not, in any way, cover any deterioration due to misuse, wear, or deterioration of other parts not supplied by us.