

Specification

PolySto PVFCF is a prefabricated full core PVC skirting 2000x8x50mmH with sloped top and skirting to wall-floor according hygienic requirements. The PVFCF skirting consists of a food grade PVC mass. Including matching accessories; prefabricated internal and external corners.

Waterproof bonding using PolySto Hard Fix Glue (Hybrid Polymere). Finishing of the joints using PolySto Food Safe Sealant or a chemical welding HygiSeal.

Available in colour white and light grey.

Consumption

Consumption Food Safe sealant (per meter)

Food Safe sealant white	800 cc
Food Safe sealant transparent	60 cc
Hard Fix Glue	115 cc
Installation m/day (8h) with 1 installer	60 meter

Consumption HygiSeal (per meter)

HygiSeal white	100 cc
Hard Fix Glue	115 cc
Installation m/day (8h) with 1 installer	30 meter

Technical info

	Kerb	Corner internal / external
Length	2.000 mm	160/160 mm
Height	50 mm	50 mm
Thickness	8 mm	8 mm
Weight	2 kg	0,36 kg
Amount / pallet	1.000 m	500 pc
Pallet size	210x80x70cmH	120x80x70cmH
Pallet weight	+- 1.050 kg	+- 200 kg

Kerb

Internal corner

External corner

